



COLUMN & BOOM SPECIFICATION										
Model	Vertical travel	Horiz: travel	Height under boom		Boom travel speed-		Trolley tra vel speed	Overall dimension		
			Max	Min	Horizontal	Vertical		Length	Width	Height
			mm	mm	mm	mm				
CB3030(P)	3000	3000	3850	850	150 -1500	750	1200	4400	150 -1500	4800
CB3030(T)	3000	3000	3850	850	150 -1500	750	1200	4400	150 -1500	4800
CB4040(P)	4000	4000	5230	1230	150 -1500	750	1200	5400	150 -1500	6330
CB4040(T)	4000	4000	5230	1230	150 -1500	750	1200	5400	150 -1500	6330
CB5050(P)	5000	5000	6250	1250	150 -1500	750	1200	6800	150 -1500	7330
CB5050(T)	5000	5000	6250	1250	150 -1500	750	1200	6800	150 -1500	7330
CB6060(P)	6000	6000	7250	1280	150 -1500	600	1200	7800	150 -1500	8330
CB6060(T)	6000	6000	7250	1280	150 -1500	600	1200	7800	150 -1500	8330

NOTE

DUE TO CONTINUOUS IMPROVEMENT, WE RESERVE THE RIGHT TO MODIFY THE DETAILS GIVEN